

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 3.1	SDS No.: 000010021749
Revision Date:	14.02.2024		1/38
Last revised date :	27.10.2022		·

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name: Hydrogen sulphide

Trade name: Hydrogen sulphide 1.8 Chemical; Hydrogen sulphide 2.5

Additional identification

Chemical name: Hydrogen sulphide

Chemical formula: H2S

INDEX No.016-001-00-4CAS-No.7783-06-4EC No.231-977-3

REACH Registration No. 01-2119445737-29

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Industrial and professional use for chemical analysis, calibration, (routine)

quality control, laboratory use. Under controlled conditions.

Industrial and professional. Perform risk assessment prior to use. Use for electronic component manufacture. Use for metal treatment. Use the gas as odorising agent in another gas (e.g. LPG). Using gas alone or in mixtures for the calibration of analysis equipment. Using gas as feedstock in chemical

processes.

Uses advised againstContact supplier for more information on uses. Uses other than those listed

above are not supported. Consumer use.

1.3 Details of the supplier of the safety data sheet

Supplier

Oy Linde Gas Ab
Telephone: +358 10 2421
Itsehallintokuja 6

FIN-02600 ESP00

E-mail: sds.ren@linde.com

1.4 Emergency telephone number: Poison Information Center: open 24 hours a day, tel. 09 471 977



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 3.1	SDS No.: 000010021749
Revision Date:	14.02.2024		2/38
Last revised date :	27.10.2022		,

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 as amended.

Physical Hazards

Flammable gas Category 1A H220: Extremely flammable gas.

Gases under pressure Liquefied gas H280: Contains gas under pressure; may explode if

heated.

Health Hazards

Acute toxicity (Inhalation - gas) Category 2 H330: Fatal if inhaled.

Specific Target Organ Toxicity - Category 3 H335: May cause respiratory irritation.

Single Exposure

Environmental Hazards

Acute hazards to the aquatic Category 1 H400: Very toxic to aquatic life.

environment

2.2 Label Elements

Contains: Hydrogen sulphide



Signal Word:

Danger

Hazard Statement(s): H220: Extremely flammable gas.

H280: Contains gas under pressure; may explode if heated.

H330: Fatal if inhaled.

H335: May cause respiratory irritation. H400: Very toxic to aquatic life.

Precautionary Statements



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 3.1	SDS No.: 000010021749
Revision Date:	14.02.2024		3/38
Last revised date :	27.10.2022		,

General None.

Prevention: P210: Keep away from heat, hot surfaces, sparks, open flames and other

> ignition sources. No smoking. P260: Do not breathe gas/vapors. P273: Avoid release to the environment.

P304+P340+P315: IF INHALED: Remove person to fresh air and keep Response:

comfortable for breathing. Get immediate medical advice/attention.

P377: Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

P381: In case of leakage, eliminate all ignition sources.

Storage: P403: Store in a well-ventilated place.

P405: Store locked up.

Disposal None.

Unknown toxicity - Health

Acute toxicity, inhalation, gas 0 %

Unknown toxicity - Environment

Acute hazards to the aquatic 100 %

environment

Chronic hazards to the aquatic

environment

100 %

Acute hazards to the aquatic

environment

0 %



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 3.1	SDS No.: 000010021749
Revision Date:	14.02.2024		4/38
Last revised date :	27.10.2022		

2.3 Other hazards

Contact with evaporating liquid may cause frostbite or freezing of skin. Not classified as PBT or vPvB.

Endocrine disrupting properties-Toxicity

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Endocrine disrupting properties-Ecotoxicity

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 3.1	SDS No.: 000010021749
Revision Date:	14.02.2024		5/38
Last revised date :	27.10.2022		

SECTION 3: Composition/information on ingredients

3.1 Substances

 Chemical name
 Hydrogen sulphide

 INDEX No.:
 016-001-00-4

 CAS-No.:
 7783-06-4

 EC No.:
 231-977-3

REACH Registration No.: 01-2119445737-29

Purity: 100%

The purity of the substance in this section is used for classification only, and does not represent the actual purity of the substance as supplied, for which other

documentation should be consulted.

Trade name: Hydrogen sulphide 1.8 Chemical; Hydrogen sulphide 2.5

Chemical name	Chemical formula	Concentration	CAS-No.		REACH Registration No.	M-Factor:	Notes
Hydrogen sulphide	H2S	100%	7783-06-4	231-977-3	01- 2119445737- 29	Aquatic Toxicity (Acute): 1	#

The concentrations of the components in the SDS header, product name on page one and in section 3.2 are in mol due to regulatory requirements. All concentrations are nominal.

SECTION 4: First aid measures

General: Remove victim to uncontaminated area wearing self contained breathing

apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if

breathing stopped.

4.1 Description of first aid measures

Inhalation: Remove victim to uncontaminated area wearing self contained breathing

apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if

breathing stopped.

[#] This substance has workplace exposure limit(s).

^{##} This substance is listed as SVHC.PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 3.1	SDS No.: 000010021749
Revision Date:	14.02.2024		6/38
Last revised date :	27.10.2022		,

Eye contact: Rinse the eye with water immediately. Remove contact lenses, if present and easy

to do. Continue rinsing. Flush thoroughly with water for at least 15 minutes. Get immediate medical assistance. If medical assistance is not immediately available,

flush an additional 15 minutes.

Skin Contact: Contact with evaporating liquid may cause frostbite or freezing of skin.

Ingestion: Ingestion is not considered a potential route of exposure.

4.2 Most important symptoms and

effects, both acute and

delayed:

May be fatal if inhaled. Contact with liquefied gas can cause damage (frostbite)

due to rapid evaporative cooling. Causes damage to organs.

4.3 Indication of any immediate medical attention and special treatment needed

Hazards: May be fatal if inhaled. Contact with liquefied gas can cause damage (frostbite)

due to rapid evaporative cooling. Causes damage to organs.

Treatment: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate

medical advice/attention. Get immediate medical advice/attention.

SECTION 5: Firefighting measures

General Fire Hazards: Heat may cause the containers to explode.

5.1 Extinguishing media

Suitable extinguishing media: Use water spray to reduce vapors or divert vapor cloud drift. Water Spray or Fog.

Dry powder. Foam.

Unsuitable extinguishing

media:

Carbon Dioxide.

5.2 Special hazards arising from the

substance or mixture:

Fire or excessive heat may produce hazardous decomposition products. Fire or

excessive heat may produce hazardous decomposition products.

Hazardous Combustion Products: If involved in a fire the following toxic and/or corrosive fumes may be produced

by thermal decomposition: Sulphur dioxide



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 3.1	SDS No.: 000010021749
Revision Date:	14.02.2024		7/38
Last revised date :	27.10.2022		

5.3 Advice for firefighters

Special fire-fighting procedures:

In case of fire: Stop leak if safe to do so. Use of water may result in the formation of very toxic aqueous solutions. Keep run-off water out of sewers and water sources. Dike for water control. Continue water spray from protected position until container stays cool. Use extinguishants to contain the fire. Isolate the source of

the fire or let it burn out.

Special protective equipment for fire-fighters:

Gas tight chemically protective clothing (Type 1) in combination with self

contained breathing apparatus.

Guideline: EN 943-2 Protective clothing against liquid and gaseous chemicals, aerosols and solid particles. Performance requirements for gas-tight (Type 1)

chemical protective suits for emergency teams (ET)

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Evacuate area. Provide adequate ventilation. Consider the risk of potentially explosive atmospheres. In case of leakage, eliminate all ignition sources. Monitor the concentration of the released product. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. EN 137 Respiratory protective devices - Self-contained opencircuit compressed air breathing apparatus with full face mask - Requirements, testing, marking.

6.2 Environmental Precautions:

Prevent further leakage or spillage if safe to do so. Reduce vapour with fog or fine water spray. Keep run-off water out of sewers and water sources. Dike for water control.

6.3 Methods and material for containment and cleaning up:

Provide adequate ventilation. Eliminate sources of ignition. Wash contaminated equipment or sites of leaks with copious quantities of water.

6.4 Reference to other sections:

Refer to sections 8 and 13.



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 3.1	SDS No.: 000010021749
Revision Date:	14.02.2024		8/38
Last revised date :	27.10.2022		·

SECTION 7: Handling and storage:

7.1 Precautions for safe handling:

Only experienced and properly instructed persons should handle gases under pressure. Avoid exposure - obtain special instructions before use. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Purge system with dry inert gas (e.g. helium or nitrogen) before gas is introduced and when system is placed out of service. Purge air from system before introducing gas. Containers, which contain or have contained flammable or explosive substances, must not be inerted with liquid carbon dioxide. Assess the risk of a potentially explosive atmosphere and the need for suitable equipment i.e. explosion-proof. Take precautionary measures against static discharges. Keep away from ignition sources (including static discharges). Provide electrical earthing of equipment and electrical equipment usable in explosive atmospheres. Use non-sparking tools. Installation of a cross purge assembly between the container and the regulator is recommended. Excess pressure must be vented through an appropriate scrubber system. Refer to supplier's handling instructions. The substance must be handled in accordance with good industrial hygiene and safety procedures. Ensure the complete system has been (or is regularly) checked for leaks before use. Protect containers from physical damage; do not drag, roll, slide or drop. Do not remove or deface labels provided by the supplier for the identification of the container contents. When moving containers, even for short distances, use appropriate equipment eq. trolley, hand truck, fork truck etc. Secure cylinders in an upright position at all times, close all valves when not in use. Provide adequate ventilation. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Avoid suckback of water, acid and alkalis. Keep container below 50°C in a well ventilated place. Observe all regulations and local requirements regarding storage of containers. When using do not eat, drink or smoke. Store in accordance with local/regional/national/international regulations. Never use direct flame or electrical heating devices to raise the pressure of a container. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. Damaged valves should be reported immediately to the supplier Close container valve after each use and when empty, even if still connected to equipment. Never attempt to repair or modify container valves or safety relief devices. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Keep container valve outlets clean and free from contaminates particularly oil and water. If user experiences any difficulty operating container valve discontinue use and contact supplier. Never attempt to transfer gases from one container to another. Container valve guards or caps



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 3.1	SDS No.: 000010021749
Revision Date:	14.02.2024		9/38
Last revised date :	27.10.2022		·

should be in place.

7.2 Conditions for safe storage, including any incompatibilities:

All electrical equipment in the storage areas should be compatible with the risk of a potentially explosive atmosphere. Segregate from oxidant gases and other oxidants being stored. Containers should not be stored in conditions likely to encourage corrosion. Stored containers should be periodically checked for general conditions and leakage. Keep away from food, drink and animal feeding stuffs. Container valve guards or caps should be in place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible material.

7.3 Specific end use(s): None.

SECTION 8: Exposure controls/personal protection

8.1 Control Parameters

Occupational Exposure Limits

Chemical name	Туре	Form of exposure	Exposure Limit Values		Source
hydrogen sulphide	TWA		5 ppm	7 mg/m3	EU. Indicative Occupational Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU, as amended (12 2009)
	STEL		10 ppm	14 mg/m3	EU. Indicative Occupational Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU, as amended (12 2009)
	HTP 15MIN		10 ppm	14 mg/m3	Finland. Workplace Exposure Limits, as amended (2009)
	HTP 8H		5 ppm	7 mg/m3	Finland. Workplace Exposure Limits, as amended (2009)

Please refer to the latest edition of the appropriate source text and consult an industrial hygienist or similar professional, or local agencies, for further information.

Biological Limit Values

No biological exposure limits noted for the ingredient(s).



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 3.1	SDS No.: 000010021749
Revision Date:	14.02.2024		10/38
Last revised date :	27.10.2022		·

DNEL-Values

Critical component	Туре	Value	Remarks
Hydrogen sulphide	Workers - Inhalation, Local,	7 mg/m3	respiratory tract irritation
	long-term		
	Workers - Inhalation,	14 mg/m3	-
	Systemic, short-term		
	Workers - Inhalation,	7 mg/m3	Repeated dose toxicity
	Systemic, long-term		
	Workers - Inhalation, Local,	14 mg/m3	-
	short-term		
	Workers - Eyes, Local effect		Hazard unknown (no further information
			necessary)

PNEC-Values

Critical component	Туре	Value	Remarks
Hydrogen sulphide	Sewage treatment plant	1,33 mg/l	-
Hydrogen sulphide	Aquatic (freshwater)	0,03 µg/l	-
Hydrogen sulphide	Aquatic (intermit. releases)	0,19 µg/l	-
Hydrogen sulphide	Aquatic (marine water)	0,003 µg/l	-
Hydrogen sulphide	Air	7 mg/m3	-

8.2 Exposure controls

Appropriate engineering controls:

Consider a work permit system e.g. for maintenance activities. Ensure adequate air ventilation. Provide adequate general and local exhaust ventilation. Keep concentrations well below occupational exposure limits. Gas detectors should be used when toxic quantities may be released. Gas detectors should be used when quantities of flammable gases or vapours may be released. Systems under pressure should be regularly checked for leakages. Product to be handled in a closed system and under strictly controlled conditions. Only use permanent leak tight installations (e.g. welded pipes). Take precautionary measures against static discharges. Do not eat, drink or smoke when using the product.



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 3.1	SDS No.: 000010021749
Revision Date:	14.02.2024		11/38
Last revised date :	27.10.2022		,

Individual protection measures, such as personal protective equipment

General information: A risk assessment should be conducted and documented in each work area to

assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered. Keep self contained breathing apparatus readily available for emergency use. Personal protective equipment for the body should be selected based on the task being performed and the risks involved. Protect eyes, face and skin from contact

with product. Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.

Eye/face protection: Safety eyewear, goggles or face-shield to EN166 should be used to avoid

exposure to liquid splashes. Wear eye protection to EN 166 when using gases.

Guideline: EN 166 Personal Eye Protection.

Skin protection

Hand Protection: Guideline: EN 388 Protective gloves against mechanical risks.

Additional Information: Wear working gloves while handling containers Guideline: EN 374-1/2/3 Protective gloves against chemicals and micro-

organisms

Additional Information: Chemically resistant gloves complying with EN 374 should

be worn at all times when handling chemical products if a risk assessment

indicates this is necessary.

Body protection: Wear fire resistant or flame retardant clothing. Keep suitable chemically resistant

protective clothing readily available for emergency use.

Guideline: ISO/TR 2801:2007 Clothing for protection against heat and flame --

General recommendations for selection, care and use of protective clothing. Guideline: EN 943 Protective clothing against liquid and gaseous

chemicals, including liquid aerosols and solid particles.

Other: Wear safety shoes while handling containers

Guideline: ISO 20345 Personal protective equipment - Safety footwear.



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 3.1	SDS No.: 000010021749
Revision Date:	14.02.2024		12/38
Last revised date :	27.10.2022		

Respiratory Protection: Reference should be made to European Standard EN 689 for methods for the

assessment of exposure by inhalation to chemical agents and national guidance documents for methods for the determination of hazardous substances. When allowed by a risk assessment Respiratory Protective Equipment (RPE) may be used The selection of the Respiratory Protective Device (RPD) must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected RPD. Self-contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen-deficient atmospheres Guideline: EN 137 Respiratory protective devices - Self-contained open-circuit compressed air breathing apparatus with full face mask - Requirements, testing,

marking.

Thermal hazards: No precautionary measures are necessary.

Hygiene measures: Obtain special instructions before use. Do not eat, drink or smoke when using the

product.

Environmental exposure

controls:

For waste disposal, see section 13 of the SDS.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state: Gas

Form: Liquefied gas Color: Colorless

Odor: Strong odor of rotten eggs

Odor Threshold: Odor threshold is subjective and is inadequate to warn of over

exposure.

Melting Point: -123 °F/-86 °C Experimental result, Key study

Boiling Point: $-76.4 \,^{\circ}\text{F}/-60.2 \,^{\circ}\text{C}$

Flammability: This product is not flammable.

Upper/lower limit on flammability or explosive limits

Explosive limit - upper: 45,5 %(V) Experimental result, Supporting study

Explosive limit - lower: 3,9 %(V)

Flash Point: Not applicable to gases and gas mixtures.

SDS FI - 000010021749



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 3.1	SDS No.: 000010021749
Revision Date:	14.02.2024		13/38
Last revised date :	27.10.2022		·

Autoignition Temperature: 270 °C Experimental result, Key study

Decomposition Temperature: When heated to decomp, emits highly toxic fumes of sulfoxides.

pH: Not applicable

Viscosity

Dynamic viscosity: 0,013 mPa.s (77 °F/25 °C) Experimental result, Not specified

Kinematic viscosity: No data available.

Solubility(ies)

Solubility in Water: 3,98 g/l

Solubility (other): No data available.

Partition coefficient (n-octanol/water): Not known.

Dispersion Stability:No data available.

Vapor pressure: 20.851 hPa (77 °F/25 °C) Experimental result, Key study

Relative density: 0,92

Density: 0,0015 g/cm3 (32 °F/0 °C)

Relative vapor density: 1,2

Particle characteristics: Not applicable

9.2 Other information

Flammability: Tci: 8,9

Minimum ignition temperature: $518 \, ^{\circ}F/270 \, ^{\circ}C$ Molecular weight: $34,08 \, g/mol \, (H2S)$

Critical Temp. (°C): 100,0 °C

SECTION 10: Stability and reactivity

10.1 Reactivity: No reactivity hazard other than the effects described in sub-section below.

10.2 Chemical Stability: Stable under normal conditions.

10.3 Possibility of hazardous Can form a potentially explosive atmosphere in air. May react violently with

reactions: oxidants.



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 3.1	SDS No.: 000010021749
Revision Date:	14.02.2024		14/38
Last revised date :	27.10.2022		

10.4 Conditions to avoid: Avoid moisture in the installation. Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No smoking.

10.5 Incompatible Materials: Air and oxidizers. Moisture. For material compatibility see latest version of ISO-

11114. With water causes rapid corrosion of some metals.

10.6 Hazardous Decomposition

Products:

Under normal conditions of storage and use, hazardous decomposition products should not be produced. If involved in a fire the following toxic and/or corrosive

fumes may be produced by thermal decomposition: Sulphur dioxide

SECTION 11: Toxicological information

General information: None.

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity - Oral

Product Based on available data, the classification criteria are not met.

Acute toxicity - Dermal

Product Based on available data, the classification criteria are not met.

Acute toxicity - Inhalation

Product

Fatal if inhaled.

Hydrogen sulphide LC 50 (Rat, 4 h): 356 ppm

Repeated dose toxicity

Hydrogen sulphide LOAEL (Rat(Female, Male), Inhalation, 90 d): 30,5 ppm(m) Inhalation

Experimental result, Key study

Skin Corrosion/Irritation

Product Based on available data, the classification criteria are not met.



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 3.1	SDS No.: 000010021749
Revision Date:	14.02.2024		15/38
Last revised date :	27.10.2022		, i

Serious Eye Damage/Eye Irritation

Product Based on available data, the classification criteria are not met.

Respiratory or Skin Sensitization

Product Based on available data, the classification criteria are not met.

Germ Cell Mutagenicity

Product Based on available data, the classification criteria are not met.

In vitro

Ames test in vitro: (OECD Guideline 471 (Bacterial Reverse Mutation Test)):

Negative.

Carcinogenicity

Product Based on available data, the classification criteria are not met.

Reproductive toxicity

Product Based on available data, the classification criteria are not met.

Reproductive toxicity (Fertility)

Fertility: Rat NOAEC: 80 ppm

Specific Target Organ Toxicity - Single Exposure

Product Route of Exposure: Inhalation

Causes irritation to the respiratory tract May cause respiratory irritation.

Specific Target Organ Toxicity - Repeated Exposure

Product Route of Exposure: Inhalation

Causes damage to the central nervous system.

Aspiration Hazard

Product Not applicable to gases and gas mixtures..

11.2 Information on other hazards

Endocrine disrupting properties



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 3.1	SDS No.: 000010021749
Revision Date:	14.02.2024		16/38
Last revised date :	27.10.2022		·

Product: The substance/mixture does not contain components considered to have

endocrine disrupting properties according to REACH Article 57(f) or Commission

Delegated regulation (EU) 2017/2100 or Commission Regulation (EU)

2018/605 at levels of 0.1% or higher.;

Components:

Hydrogen sulphide The substance/mixture does not contain components considered to have

endocrine disrupting properties according to REACH Article 57(f) or Commission

Delegated regulation (EU) 2017/2100 or Commission Regulation (EU)

2018/605 at levels of 0.1% or higher.;

Other information

Product: No data available.

SECTION 12: Ecological information

General information: Very toxic to aquatic organisms. Endangering to drinking water. Avoid release to

the environment. Product is not allowed to be discharged into ground water or the

aquatic environment. Not applicable

12.1 Toxicity

Acute toxicity

Product Toxic to aquatic organisms. Very toxic to aquatic life.

12.2 Persistence and Degradability

Product Not applicable to gases and gas mixtures..

Biodegradation

Inorganic The product is not readily biodegradable.

12.3 Bioaccumulative potential

Product The substance has no potential for bioaccumulation.

12.4 Mobility in soil

Product The substance has low mobility in soil.

12.5 Results of PBT and vPvB

assessment

Product Not classified as PBT or vPvB.



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 3.1	SDS No.: 000010021749
Revision Date:	14.02.2024		17/38
Last revised date :	27.10.2022		·

Other Ecological Information

May cause pH changes in aqueous ecological systems. Depending on local conditions and existing concentrations, disturbances in the biodegradation process

of activated sludge are possible.

12.6 Endocrine disrupting properties:

Product: The substance/mixture does not contain components considered to have

endocrine disrupting properties according to REACH Article 57(f) or Commission

Delegated regulation (EU) 2017/2100 or Commission Regulation (EU)

2018/605 at levels of 0.1% or higher.

Components:

Hydrogen sulphide The substance/mixture does not contain components considered to have

endocrine disrupting properties according to REACH Article 57(f) or Commission

Delegated regulation (EU) 2017/2100 or Commission Regulation (EU)

2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects:

Other hazards

Product: No data available.

Other effects:

SECTION 13: Disposal considerations

13.1 Waste treatment methods

General information: Must not be discharged to atmosphere. Consult supplier for specific

recommendations.

Disposal methods: Refer to the EIGA code of practice (Doc.30 "Disposal of Gases", downloadable at

http://www.eiga.org) for more guidance on suitable disposal methods. Dispose of container via supplier only. Discharge, treatment, or disposal may be subject to

national, state, or local laws.

European Waste Codes

Container: 16 05 04*: Gases in pressure containers (including halons) containing

hazardous substances.

Making our world more productive



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 3.1	SDS No.: 000010021749
Revision Date:	14.02.2024		18/38
Last revised date :	27.10.2022		,

SECTION 14: Transport information

ADR

14.1 UN number or ID number: UN 1053

14.2 UN Proper Shipping Name: HYDROGEN SULPHIDE

14.3 Transport Hazard Class(es)

Class: 2
Label(s): 2.3, 2.1
Hazard No. (ADR): 263
Tunnel restriction code: (B/D)

14.4 Packing Group:

Limited quantity

Excepted quantity

None.

14.5 Environmental hazards: Environmentally Hazardous

14.6 Special precautions for user:

RID

14.1 UN number or ID number: UN 1053

14.2 UN Proper Shipping Name HYDROGEN SULPHIDE

14.3 Transport Hazard Class(es)

Class: 2
Label(s): 2.3, 2.1

14.4 Packing Group: Limited quantity None.

Excepted quantity None.

14.5 Environmental hazards: Environmentally Hazardous

14.6 Special precautions for user: –

Making our world more productive



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 3.1	SDS No.: 000010021749
Revision Date:	14.02.2024		19/38
Last revised date :	27.10.2022		·

IMDG

14.1 UN number or ID number: UN 1053

14.2 UN Proper Shipping Name: HYDROGEN SULPHIDE

14.3 Transport Hazard Class(es)

 Class:
 2.3

 Label(s):
 2.3, 2.1

 EmS No.:
 F-D, S-U

14.4 Packing Group: -

Limited quantity None. Excepted quantity None.

14.5 Environmental hazards: Not applicable

14.6 Special precautions for user:

IATA

14.1 UN number or ID number: UN 1053

14.2 Proper Shipping Name: Hydrogen sulphide

14.3 Transport Hazard Class(es):

Class: 2.3
Label(s):
14.4 Packing Group: Limited quantity None.

Excepted quantity None.

14.5 Environmental hazards: Environmentally Hazardous

14.6 Special precautions for user: –

Other information

Passenger and cargo aircraft: Forbidden. Cargo aircraft only: Forbidden.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 3.1	SDS No.: 000010021749
Revision Date:	14.02.2024		20/38
Last revised date :	27.10.2022		

Additional identification:

Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers ensure that they are firmly secured. Ensure that the container valve is closed and not leaking. Container valve guards or caps should be in place. Ensure adequate air ventilation.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

EU Regulations

EU. REACH Annex XIV, Substances Subject to Authorization as amended: None present or none present in regulated quantities.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended: None present or none present in regulated quantities.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended: None present or none present in regulated quantities.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended: None present or none present in regulated quantities.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended: None present or none present in regulated quantities.

Regulation (EC) No. 1907/2006 Annex XVII Substances subject to restriction on marketing and use:

Chemical name	CAS-No.
Hydrogen sulphide	7783-06-4

EU. Directive 2012/18/EU (SEVESO III) on major accident hazards involving dangerous substances, Annex I:

Chemical	CAS-No.	Lower-tier	Upper-tier
		Requirements	Requirements
Hydrogen sulphide	7783-06-4	5 t	20 t



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 3.1	SDS No.: 000010021749
Revision Date:	14.02.2024		21/38
Last revised date :	27.10.2022		·

Directive 98/24/EC on the protection of workers from the risks related to chemical agents at work:

Chemical name	CAS-No.	Concentration
Hydrogen sulphide	7783-06-4	100%

National Regulations

Council Directive 89/391/EEC on the introduction of measures to encourage improvements in the safety and health of workers at work Directive 2016/425/EEC on personal protective equipment Directive 2014/34/EU on equipment and protective systems intended for use in potentially explosive atmospheres (ATEX) Only products that comply with the food regulations (EC) No. 1333/2008 and (EU) No. 231/2012 and are labelled as such may be used as food additives.

This Safety Data Sheet has been produced to comply with Regulation (EU) 2020/878.

15.2 Chemical safety assessment: Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Revision Information: Relevant changes are indicated using two vertical bold lines and red text, the text is

also highlighted in grey.

Abbreviations and acronyms:

ECTLV: EU. Indicative Occupational Exposure Limit Values in Directives 91/322/EEC,

2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU, as amended

FN_OEL: Finland. Workplace Exposure Limits, as amended

ECTLV / STEL: Short Term Exposure Limit (STEL): ECTLV / TWA: Time Weighted Average (TWA): FN_OEL / HTP 15MIN: Short Term Exposure Limit (STEL): FN_OEL / HTP 8H: Time Weighted Average (TWA):

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging

Making our world more productive



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 3.1	SDS No.: 000010021749
Revision Date:	14.02.2024		22/38
Last revised date :	27.10.2022		·

Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; EIGA - European Industrial Gases Association; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China: IMDG - International Maritime Dangerous Goods: IMO - International Maritime Organization: ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR -(Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 3.1	SDS No.: 000010021749
Revision Date:	14.02.2024		23/38
Last revised date :	27.10.2022		,

Key literature references and sources for data:

Various sources of data have been used in the compilation of this SDS, they include but are not exclusive to:

Agency for Toxic Substances and Diseases Registry (ATSDR)

(http://www.atsdr.cdc.gov/).

European Chemical Agency: Guidance on the Compilation of Safety Data Sheets.

European Chemical Agency: Information on Registered Substances http://apps.echa.europa.eu/registered/registered-sub.aspx#search

European Industrial Gases Association (EIGA) Doc. 169 "Classification and Labelling quide". as amended.

International Programme on Chemical Safety (http://www.inchem.org/) ISO 10156:2010 Gases and gas mixtures - Determination of fire potential and oxidizing ability for the selection of cylinder valve outlets.

Matheson Gas Data Book, 7th Edition.

National Institute for Standards and Technology (NIST) Standard Reference Database Number 69.

The ESIS (European chemical Substances 5 Information System) platform of the former European Chemicals Bureau (ECB) ESIS (http://ecb.jrc.ec.europa.eu/esis/). The European Chemical Industry Council (CEFIC) ERICards.

United States of America's National Library of Medicine's toxicology data network

TOXNET (http://toxnet.nlm.nih.gov/index.html)

Threshold Limit Values (TLV) from the American Conference of Governmental Industrial Hygienists (ACGIH).

Substance specific information from suppliers.

Details given in this document are believed to be correct at the time of publication.

Wording of the H-statements in section 2 and 3

H220	Extremely flammable gas.
H280	Contains gas under pressure; may explode if heated.
H330	Fatal if inhaled.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.

Training information:

Users of breathing apparatus must be trained. Ensure operators understand the toxicity hazard. Ensure operators understand the flammability hazard. Ensure operators understand the hazards.



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 3.1	SDS No.: 000010021749
Revision Date:	14.02.2024		24/38
Last revised date :	27.10.2022		

Classification according to Regulation (EC) No 1272/2008 as amended.

Flam. Gas 1A, H220

Press. Gas Liq. Gas, H280

Acute Tox. 2, H330 STOT SE 3, H335

Aquatic Acute 1, H400

Other information: Before using this product in any new process or experiment, a thorough material

compatibility and safety study should be carried out. Ensure adequate air ventilation. Ensure all national/local regulations are observed. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting

from its use can be accepted.

Last revised date: 14.02.2024

Disclaimer: This information is provided without warranty. The information is believed to be

correct. This information should be used to make an independent determination of

the methods to safeguard workers and the environment.



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 3.1	SDS No.: 000010021749
Revision Date:	14.02.2024		25/38
Last revised date :	27.10.2022		·

Annex to the extended Safety Data Sheet (eSDS)

Content

Exposure Scenario 1. Industrial use, Formulation of mixtures with gas in pressure receptacles,

Transfilling gas or liquid., Use the gas as odorising agent in another gas (e.g.

LPG)., Using gas for metal treatment., Use for electronic component

manufacture., Using gas as feedstock in chemical processes.

Exposure Scenario 2. Professional use, Using gas alone or in mixtures for the calibration of analysis

equipment.

Exposure Scenario 1.

Exposure scenario worker

1. Industrial use, Formulation of mixtures with gas in pressure receptacles, Transfilling gas or liquid., Use the gas as odorising agent in another gas (e.g. LPG)., Using gas for metal treatment., Use for electronic component manufacture., Using gas as feedstock in chemical processes.

List of use descriptors	
Sector(s) of use	SU0: Other
	SU4: Manufacture of food products
	SU8: Manufacture of bulk, large scale chemicals (including petroleum products)
	SU9: Manufacture of fine chemicals
	SU11: Manufacture of rubber products
	SU15: Manufacture of fabricated metal products, except machinery and equipment
	SU16: Manufacture of computer, electronic and optical products, electrical equipment
Product categories [PC]:	PC2: Adsorbents



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 3.1	SDS No.: 000010021749
Revision Date:	14.02.2024		26/38
Last revised date :	27.10.2022		·

PC14: Metal surface treatment products
PC21: Laboratory chemicals
PC33: Semiconductors

Name of contributing environmental scenario and corresponding ERC	Industrial use: ERC2: Formulation into mixture	
	ERC6a: Use of intermediate	
	ERC6b: Use of reactive processing aid at industrial site (no inclusion into or onto article)	
	ERC7: Use of functional fluid at industrial site	

Contributing Scenarios	Industrial use: PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions PROC3: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC9: Transfer of substance or mixture into small containers (dedicated filling line, including weighing)
	PROC16: Use of fuels

2.1. Contributing exposure scenario controlling environmental exposure for: Industrial use



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 3.1	SDS No.: 000010021749
Revision Date:	14.02.2024		27/38
Last revised date :	27.10.2022		·

Product characteristics	
Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
Physical form of the product	See section 9 of the SDS.
Viscosity:	
Kinematic viscosity:	No data available.
Dynamic viscosity:	0,013 mPa.s (77 °F/25 °C)
Amounts used	
A a contact and a second	TO 4
Annual amount per site	50 t
Frequency and duration of use	
Batch process:	not relevant
Continuous process:	260 Emission days

Environment factors not influenced by risk management

Flow rate of receiving surface water (m³/d):	Local freshwater dilution factor	Local marine water dilution factor	Other factors:	Remarks:
18.000 m3/d	not relevant	not relevant	Assumed on-site sewage treatment plant flow (m3/d):	Estimated 2000 m3/day

Other given operational conditions affecting environmental exposure

tuno	Emission days	Emission factors			Domasks
type	Emission days	Air	Soil	Water	Remarks
Continuous release	260	95 %	-	-	Closed systems are used in order to prevent unintended emissions



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 3.1	SDS No.: 000010021749
Revision Date:	14.02.2024		28/38
Last revised date :	27.10.2022		·

Other relevant operational conditions	not relevant

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See chapter 8 of the safety data sheet (Environmental exposure controls).

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Technical and organisational measures	Closed systems are used in order to prevent unintended emissions
Air	not relevant
Soil	not relevant
Water	not relevant
Remarks:	Soil emission controls are not applicable as there is no direct release to soil.

Organisational measures to prevent/limit release from site:

none

Conditions and measures related to sewage treatment plant

type:	Municipal Sewage Treatment Plant	
Discharge rate:	not relevant	
Treatment effectiveness:	not relevant	
Sludge treatment technique:	not relevant	
Measures to limit air emissions:	not relevant	
Remarks:	Direct emissions to the municipal STP should not be made.	

Conditions and measures related to external treatment of waste for disposal

Fraction of used amount transferred to external waste treatment:

Suitable waste treatment	Treatment effectiveness	Remarks
--------------------------	-------------------------	---------



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 3.1	SDS No.: 000010021749
Revision Date:	14.02.2024		29/38
Last revised date :	27.10.2022		·

External treatment and disposal of waste
should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Fraction of used amount transferred to external waste treatment:

Suitable recovery operations:	Treatment effectiveness	Remarks
See section 13 of the SDS		External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice beyond the REACH CSA

Use appropriate abatement systems to ensure that the emission levels defined by local regulations are not exceeded. Ensure operatives are trained to minimise releases

2.2. Contributing exposure scenario controlling worker exposure for: Industrial use

Process Categories:	PROC1: Chemical production or refinery in closed process without
	likelihood of exposure or processes with equivalent containment
	conditions
	PROC3: Manufacture or formulation in the chemical industry in closed
	batch processes with occasional controlled exposure or processes with
	equivalent containment condition
	PROC8b: Transfer of substance or mixture (charging and discharging)
	at dedicated facilities
	PROC9: Transfer of substance or mixture into small containers
	(dedicated filling line, including weighing)
	PROC16: Use of fuels

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.		
Physical form of the product:	See section 9 of the SDS.		



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 3.1	SDS No.: 000010021749
Revision Date:	14.02.2024		30/38
Last revised date :	27.10.2022		

Vapour pressure:	20851 hPa
Process temperature:	25 °C
Remarks	not relevant

Amounts used

Daily amount per site	The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation (industrial vs. professional) and level of containment/automation (as reflected in the PROCs and technical conditions) is the main determinant of the process-intrinsic emission potential.
-----------------------	--

Frequency and duration of use

	Use duration:	Frequency of use:	Remarks
Hours per shift	<= 8 h	5 days per week	PROC1, PROC3, PROC8b, PROC9, PROC16

Human factors not influenced by risk management

This information is not available.

Other given operational conditions affecting workers exposure

Area of use	Room size:	Temperature:	Ventilation rate	Remarks
Indoor or outdoor use				Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions, Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition, Transfer of substance or mixture (charging and discharging) at dedicated facilities, Transfer of substance or mixture into small containers (dedicated filling line, including weighing), Use of fuels



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 3.1	SDS No.: 000010021749
Revision Date:	14.02.2024		31/38
Last revised date :	27.10.2022		·

Other relevant operational conditions:. See section 8 of the SDS.							
Risk management me	easures (RMM)						
Technical conditions	and measures at proce	ss level (source) to pro	event release				
See chapter 7 of t	the safety data sheet						
Technical conditions	and measures to contro	ol dispersion from sou	rce towards the work	ēt .			
inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks			
See chapter 7 of the safety data sheet				Undertake operation under enclosed conditions.			
Organisational meas	ures to prevent/limit re	eleases, dispersion an	d exposure				
inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks			
				See section 7 of the SDS.			
Conditions and measures related to personal protection, hygiene and health evaluation							
inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks			
				See chapter 8 of the safety data sheet (Personal protection equipment)			

See section 7 of the SDS. Handle product within a closed system. Drain down and flush system prior to equipment break-in or maintenance. Apply a good standard of general or controlled ventilation when maintenance activities are

carried out.

Additional good practice advice beyond the REACH CSA



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 3.1	SDS No.: 000010021749
Revision Date:	14.02.2024		32/38
Last revised date :	27.10.2022		

3. Exposure estimation			
Environment:			
Industrial use:			
none			
Health: Industrial use:			
none			

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

Check that RMMs and OCs are as described above or of equivalent efficiency Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see http://www.ecetoc.org/tra

Exposure Scenario 2.

Exposure scenario worker

1. Professional use, Using gas alone or in mixtures for the calibration of analysis equipment.

List of use descriptors	
Sector(s) of use	SU0: Other
Product categories [PC]:	PC21: Laboratory chemicals
Name of contributing environmental scenario and corresponding ERC	Using gas alone or in mixtures for the calibration of analysis equipment.: ERC8b: Widespread use of reactive processing aid (no inclusion into or onto article, indoor)
Contributing Scenarios	Using gas alone or in mixtures for the calibration of analysis equipment.: PROC15: Use as laboratory reagent



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 3.1	SDS No.: 000010021749
Revision Date:	14.02.2024		33/38
Last revised date :	27.10.2022		

2.1. Contributing exposure scenario controlling environmental exposure for: Using gas alone or in mixtures for the calibration of analysis equipment.					
Product characteristics					
Concentration of the substance in a mixture: Covers percentage substance in the product up to 100 %.				p to 100 %.	
Physical form of the pro	oduct	See section 9 of the	SDS.		
Viscosity:					
Kinematic viscosity:		No data available.			
Dynamic viscosity:		0,013 mPa.s (77 °F/	0,013 mPa.s (77 °F/25 °C)		
Amounts used	Amounts used				
Annual amount per site	Annual amount per site 10 kg				
Frequency and duration of use					
Batch process:		260 Emission days			
Continuous process:		not relevant	not relevant		
Environment factors not influenced by risk management					
Flow rate of receiving surface water (m³/d):	Local freshwater dilution factor	Local marine water dilution factor Other factors: Remarks:			
18.000 m3/d	not relevant	not relevant	Assumed on-site sewage treatment plant flow (m3/d):	Estimated 2000 m3/day	

Emission factors

Remarks

type

Other given operational conditions affecting environmental exposure

Emission days



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 3.1	SDS No.: 000010021749
Revision Date:	14.02.2024		34/38
Last revised date :	27.10.2022		·

		Air	Soil	Water	
Intermittent release	260	95 %	-	-	Closed systems are used in order to prevent unintended emissions

Other relevant operational conditions	not relevant
---------------------------------------	--------------

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See chapter 8 of the safety data sheet (Environmental exposure controls).

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Technical and organisational measures	Closed systems are used in order to prevent unintended emissions
Air	not relevant
Soil	not relevant
Water	not relevant
Remarks:	Soil emission controls are not applicable as there is no direct release to soil.

Organisational measures to prevent/limit release from site:

none

Conditions and measures related to sewage treatment plant

type:	Municipal Sewage Treatment Plant	
Discharge rate:	not relevant	
Treatment effectiveness:	not relevant	
Sludge treatment technique:	not relevant	
Measures to limit air emissions:	not relevant	
Remarks:	Direct emissions to the municipal STP should not be made.	



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 3.1	SDS No.: 000010021749
Revision Date:	14.02.2024		35/38
Last revised date :	27.10.2022		·

Conditions and measures related to external treatment of waste for disposal

Fraction of used amount transferred to external waste treatment:

Suitable waste treatment	Treatment effectiveness	Remarks
See section 13 of the SDS		External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Fraction of used amount transferred to external waste treatment:

Suitable recovery operations:	Treatment effectiveness	Remarks
See section 13 of the SDS		External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice beyond the REACH CSA

Use appropriate abatement systems to ensure that the emission levels defined by local regulations are not exceeded. Ensure operatives are trained to minimise releases

2.2. Contributing exposure scenario controlling worker exposure for: Using gas alone or in mixtures for the calibration of analysis equipment.

Process Categories:	PROC15: Use as laboratory reagent
Product characteristics	
Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.
Physical form of the product:	See section 9 of the SDS.
Vapour pressure:	20851 hPa
Process temperature:	25 °C
Remarks	not relevant



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 3.1	SDS No.: 000010021749
Revision Date:	14.02.2024		36/38
Last revised date :	27.10.2022		

Amounts used						
Daily amount per site		The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation (industrial vs. professional) and level of containment/automation (as reflected in the PROCs and technical conditions) is the main determinant of the process-intrinsic emission potential.				
Frequency and durat	ion of use					
Hours per shift		e duration: 8 h		quency of use: ays per week	Remarks PROC15	
Human factors not in	fluenced by risk	management	t			
	This information is not available. Other given operational conditions affecting workers exposure					
Area of use Indoor use	Room size:	Temperatur	e:	Ventilation rate	Remarks Use as laboratory reagent	
Other relevant operational conditions: . See section 8 of the SDS.						
Risk management measures (RMM)						
Technical conditions and measures at process level (source) to prevent release						
See chapter 7 of the safety data sheet						
Technical conditions and measures to control dispersion from source towards the worker						

eye exposure

oral exposure

Remarks

dermal exposure

inhalation

exposure



According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 3.1	SDS No.: 000010021749
Revision Date:	14.02.2024		37/38
Last revised date :	27.10.2022		·

See chapter 7 of the		Undertake operation under
safety data sheet		enclosed conditions.

Organisational measures to prevent/limit releases, dispersion and exposure

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
				See section 7 of the SDS.

Conditions and measures related to personal protection, hygiene and health evaluation

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
				See chapter 8 of the safety data sheet (Personal protection equipment)

Additional good practice advice beyond the REACH CSA

See section 7 of the SDS. Handle product within a closed system. Drain down and flush system prior to equipment break-in or maintenance. Apply a good standard of general or controlled ventilation when maintenance activities are carried out.

3. Exposure estimation

Environment:

Using gas alone or in mixtures for the calibration of analysis equipment.:

none

Health:

Using gas alone or in mixtures for the calibration of analysis equipment.:

none

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

Check that RMMs and OCs are as described above or of equivalent efficiency Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific

Making our world more productive



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Hydrogen sulphide

Issue Date:	16.01.2013	Version: 3.1	SDS No.: 000010021749
Revision Date:	14.02.2024		38/38
Last revised date :	27.10.2022		·

risk management measures. For scaling see http://www.ecetoc.org/tra